



12-STRAND DYNEEMA

Manufactured with Dyneema® fibre and coated with polyurethane this 12-Strand braided rope is an excellent alternative to steel cable. This rope has extremely high strength, low stretch and is light weight. The polyurethane coating adds additional abrasion resistance for longer life.

CHARACTERISTICS

- Extremely high strength
- Light Weight
- Abrasion resistant
- Low Stretch
- Floats on water
- Splicable
- Wear resistant
- Flexible



APPLICATIONS

- Winch Lines
- Tow Lines
- Alternate to steel cable
- Rigging Lines
- Utility Line

Standard Polyurethane coating is orange, other colours available depending on order. Standard lengths are 600' and 1200' with or without splices and / or hooks.

Please contact us for additional information and specifications.

Please see our Dyneema Miniline for smaller diameter dyneema lines

SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/600'	WEIGHT/600'
02048	3/16	4.8	4600 LBS	2100 KG		
02064	1/4	6.0	7500 LBS	3400 KG		
02079	5/16	7.9	12000 LBS	5400 KG		
02095	3/8	9.5	18000 LBS	8100 KG		
02111	7/16	11.1	22500 LBS	10200 KG		
02127	1/2	12.7	31000 LBS	14000 KG		
02143	9/16	14.3	37000 LBS	16000 KG		
02159	5/8	15.9	47000 LBS	21000 KG		
02191	3/4	19.1	58000 LBS	26000 KG		

ATLANTIC BRAIDS LTD.

100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA

TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192

