



# 12-STRAND POLYESTER

Manufactured from 100% high tenacity continuous filament polyester. This product is constructed as a single or hollow braid and is high strength, low stretch and abrasion resistant. 12-Strand Polyester is easy to splice and can be coated with polyurethane.

## FEATURES

- High strength
- Low stretch
- Abrasion resistant
- Spliceable

## APPLICATIONS

- Climbing line
- Rigging Line
- Utility Line



Standard lengths are 600 and 1200ft.

Please contact us for additional information including alternative colours or specifications.

## SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/600'	WEIGHT/600'
01048	3/16	4.8	1200 LBS	544 KG		
01064	1/4	6.4	2200 LBS	998 KG		
01079	5/16	7.9	3200 LBS	1451 KG		
01095	3/8	9.5	5000 LBS	2268 KG	26 LBS	12 KG
01111	7/16	11.1	8000 LBS	3629 KG		
01127	1/2	12.7	11000 LBS	4989 KG	48 LBS	22 KG
01159	5/8	15.9	16000 LBS	7257 KG	77 LBS	35 KG
01191	3/4	19.1	21000 LBS	9525 KG	105 LBS	48 KG
01222	7/8	22.2	30000 LBS	13607 KG		
01254	1	25.4	36500 LBS	16556 KG		
01286	1 1/8	28.6	48500 LBS	21999 KG		
01318	1 1/4	31.8	56000 LBS	25401 KG		
01334	1 5/16	33.4	65000 LBS	29484 KG		
01349	1 3/8	34.9	71000 LBS	32205 KG		
01381	1 1/2	38.1	82000 LBS	37194 KG		
01413	1 5/8	41.3	98000 LBS	44452 KG		
01445	1 3/4	44.5	110000 LBS	49900 KG		

**ATLANTIC BRAIDS LTD.**

**100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA**

**TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192**

**www.atlanticbraids.com**