



# DOUBLE BRAID MFP

Double braid multi-filament polypropylene is constructed with a 100% MFP braided cover and core. The product is available in a multitude of colour combinations is low stretch and lightweight. Other characteristics include the ability to float on water, UV resistance as well as oil and mildew resistant. Excellent for use as a rescue line or as a crowd control line.

## FEATURES

- High strength
- Lightweight
- Durability
- Splicability
- Abrasion resistant
- UV resistant
- Not affected by oil, grease, gasoline, or mildew



## APPLICATIONS

- Rescue line
- Crowd control line

Standard lengths are 600ft and 1200ft.

Please contact us for additional information including alternative colours or specifications.

## SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/1000'	WEIGHT/1000'
24048	3/16	4.8			8.8 LBS	4 KG
24064	1/4	6.4	700 LBS	317 KG	12 LBS	5.5 KG
24079	5/16	7.9	1000 LBS	453 KG	21 LBS	9.5 KG
24095	3/8	9.5	1600 LBS	725 KG	30 LBS	14 KG
24111	7/16	11.1	2100 LBS	952 KG	39 LBS	18 KG
24127	1/2	12.7	2500 LBS	1133 KG	48 LBS	<b>22 KG</b>
24143	9/16	14.3				
24159	5/8	15.9	10300 LBS	4672 KG	92 LBS	42 KG
24191	3/4	19.1	13000 LBS	5896 KG	123 LBS	56 KG
24222	7/8	22.2	19000 LBS	8618 KG		
24254	1	25.4	22600 LBS	10251 KG	227 LBS	103 KG
24286	1 1/8	28.6				
24318	1 1/4	31.8				

ATLANTIC BRAIDS LTD.

100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA  
TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192