

ANCHOR & DOCK LINES

Both the Anchor and Dock lines are constructed from our Double Braid Nylon which is constructed with a braided nylon cover over a braided nylon core. The Double Braid construction increases the strength and decreases the elongation of the rope which makes it ideal to be used as an all purpose utility rope or marine line. All our Double Braid Nylon meets the Canadian government spec. CGSB 40.16.95.

FEATURES

- High Strength
- Medium Elongation
- Abrasion Resistant
- Splicable
- Excellent shock absorption

APPLICATIONS

- Anchor Line
- Dock Line
- Towing Rope



Standard lengths for anchor lines are 100ft, 150ft, 200ft, 300ft and 350ft. One end is heat sealed the other is spliced. Standard lengths for dock lines begin at 10ft through to 45ft in increments of 5ft. (min. order of 10 units) All dock lines hand spliced at one end and heat sealed at the other.

Please contact us for additional information or specifications.

SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/600'	WEIGHT/600'
ANCHOR LINES						
20095AL	3/8"	9.5	4100 LBS	1800 KG	24 LBS	11 KG
20127AL	1/2"	12.7	7400 LBS	3300 KG	37 LBS	17 KG
20159AL	5/8"	15.9	13000 LBS	5900 KG	68 LBS	31 KG
DOCK LINES						
20095DL	3/8"	9.5	4100 LBS	1800 KG	24 LBS	11 KG
20127DL	1/2"	12.7	7400 LBS	3300 KG	37 LBS	17 KG
20159DL	5/8"	15.9	13000 LBS	5900 KG	68 LBS	31 KG
20191DL	3/4"	19.1	16000 LBS	7200 KG	92 LBS	42 KG

ATLANTIC BRAIDS LTD.
 100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA
 TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192

