



# DOUBLE BRAID NYLON

Manufactured from 100% nylon yarn this product is constructed with a braided core and cover. The result is a product which has high strength, controlled stretch and is abrasion resistant. Our DBN meets the Canadian government spec (40-GP 16M Type 1).

## FEATURES

High Strength  
Controlled Stretch  
Abrasion resistant  
Easily spliced  
excellent shock absorption

## APPLICATIONS

Dock and Anchor lines  
Tow Lines  
Slings  
Lifer-Lines  
General utility



Standard lengths are 600ft and 1200ft.

Please contact us for additional information including alternative colours or specifications.

## SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/600'	WEIGHT/600'
20064	1/4	6.4	2100 LBS	952 KG	10 LBS	4.5 KG
20079	5/16	7.9	3400 LBS	1542 KG	14 LBS	6.3 KG
20095	3/8	9.5	4800 LBS	2177 KG	24 LBS	11.2 KG
20111	7/16	11.1	6500 LBS	2948 KG	33 LBS	14.9 KG
20127	1/2	12.7	8300 LBS	3765 KG	39 LBS	<b>17.5 KG</b>
20143	9/16	14.3	11700 LBS	5307 KG	45 LBS	20 KG
20159	5/8	15.9	15200 LBS	6894 KG	69 LBS	31 KG
20191	3/4	19.1	19100 LBS	8663 KG	93 LBS	42 KG
20222	7/8	22.2	26000 LBS	11793 KG	131 LBS	59 KG
20254	1	25.4	31000 LBS	14061 KG	165 LBS	75 KG
20286	1 1/8	28.6	42500 LBS	19277 KG	198 LBS	90 KG
20318	1 1/4	31.8	52000 LBS	23586 KG	257 LBS	117 KG
20349	1 3/8	34.9	60000 LBS	27215 KG		
20381	1 1/2	38.1	72000 LBS	32658 KG	359 LBS	163 KG
20413	1 5/8	41.3	84000 LBS	38101 KG		
20445	1 3/4	44.5	100000 LBS	45359 KG	489 LBS	222 KG

**ATLANTIC BRAIDS LTD.**

**100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA  
TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192**