



# DYNAMIC Industrial Climbing & Decent Lines

Manufactured on a 32 carrier Kermantle braider these industrial climbing and decent ropes are dynamic. The dynamic characteristic is achieved by manufacturing the core of the rope as a combination of twisted and cabled nylon. The result is a rope which will elongate and absorb energy of in case of a fall.

## FEATURES

- high strength
- Abrasion Resistant
- Hard wearing
- UV Resistant



Twisted & cabled core



## APPLICATIONS

Industrial climbing and Decent Line

This product is available in a variety of colours.  
Please contact us for additional information or additional specifications.

## SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/600'	WEIGHT/600'
61048	3/16	4.8	1200 LBS	544 KG		
61064	1/4	6.4	2400 LBS	1088 KG	11.5 LBS	5.2 KG
61079	5/16	7.9	3800 LBS	1720 KG	17.3 LBS	7.85 KG
61095	3/8	9.5	5800 LBS	2630 KG	28.0 LBS	12.72 KG
61111	7/16	11.1	6800 LBS	3084 KG	34.4 LBS	15.62 KG
61127	1/2	12.7	8800 LBS	3990 KG	48.5 LBS	22 KG
61143	9/16	14.3	10200 LBS	4626 KG		
61159	5/8	15.9	12500 LBS	5669 KG		
61191	3/4	19.1	15000 LBS	6803 KG		
61222	7/8	22.2				
61254	1	25.4				

ATLANTIC BRAIDS LTD.  
100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA  
TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192  
[www.atlanticbraids.com](http://www.atlanticbraids.com)