



# General Purpose Sash Braid Nylon

A smooth surfaced general purpose sash braid manufactured from 100% continuous filament Nylon. Sometimes called a "solid braid" because the strands cross and fill the center of the cord. These cords can also be combined with a core of galvanized wire or synthetic fibre for increased strength and durability.

## FEATURES

- High shock absorption
- Abrasion Resistance
- High Strength
- Flexible and easy to handle
- Easy knotting
- Not Splicable

## APPLICATIONS

- Pulley line
- Winch Line
- Utility Line



Standard lengths are 250ft, 500ft, and 1000ft.

Please contact us for additional information including alternative colours or specifications.

## SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/1000'	WEIGHT/1000'
40032GP	1/8	3.2	500 LBS	226 KG		
40040GP	5/32	4.0	700 LBS	317 KG	6.28 LBS	2.85 KG
40044GP	11/64	4.4	780 LBS	353 KG	7.39 LBS	3.35 KG
40048GP	3/16	4.8	915 LBS	415 KG	10.49 LBS	4.76 KG
40064GP	1/4	6.4	1475 LBS	669 KG	13 LBS	6.34 KG
40079GP	5/16	7.9	1855 LBS	841 KG	22 LBS	10 KG
40095GP	3/8	9.5	2800 LBS	1270 KG	37 LBS	17.2 KG
40111GP	7/16	11.1	4000 LBS	1814 KG		
40127GP	1/2	12.7	6000 LBS	2721 KG	54 LBS	24.5 KG
40143GP	9/16	14.3	7500 LBS	3401 KG		
40159GP	5/8	15.9	9000 LBS	4082 KG		
40191GP	3/4	19.1	11000 LBS	4989 KG		

ATLANTIC BRAIDS LTD.

100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA

TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192

[www.atlanticbraids.com](http://www.atlanticbraids.com)