



SOLID BRAID NYLON

Manufactured by braiding a 16 strand 2-over-1 nylon cover over a parallel nylon fiber core. The parallel fibers impart increased strength and durability to this non-splicable low stretch cord.

FEATURES

- Excellent abrasion resistance
- Good strength to weight ratio
- Easy knotting
- Lower stretch due to parallel core not splicable

APPLICATIONS

- Utility cord
- Tent / tarpaulin cord
- Flag pole lines
- tie down



Standard lengths are 250ft, 500ft, and 1000ft.

Please contact us for additional information including alternative colours or specifications.

SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/1000'	WEIGHT/1000'
50016	1/16	1.6	270 LBS	122 KG	1.43 LBS	0.65 KG
50024	3/32	2.4	380 LBS	172 KG	2.71 LBS	1.23 KG
50028	7/64	2.8	566 LBS	256 KG	3.86 LBS	1.75 KG
50032	1/8	3.2	600 LBS	272 KG	5.22 LBS	2.37 KG
50036	9/64	3.6	630 LBS	285 KG		
50040	5/32	4.0	733 LBS	332 KG	7.94 LBS	3.6 KG
50044	11/64	4.4	875 LBS	396 KG		
50048	3/16	4.8	1080 LBS	489 KG	10.14 LBS	4.6 KG
50052	13/64	5.2	1120 LBS	508 KG		
50056	7/32	5.6	1250 LBS	567 KG	11.9 LBS	5.4 KG
50064	1/4	6.4	1460 LBS	662 KG	15.43 LBS	7 KG

ATLANTIC BRAIDS LTD.

100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA

TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192

www.atlanticbraids.com