



STARTER CORD

Manufactured from 100% continuous filament nylon this cord has superb elongation and excellent shock absorbing ability. A smooth surfaced, high wear resistant, uniformly round solid braid. Excellent for use as a starter cord for anything from a lawn mower to a chain saw, Is manufactured to a precise diameter.

FEATURES

- High Strength
- High Elongation
- Excellent abrasion resistance
- Excellent shock absorption
- Hard wearing
- Uniformly round

APPLICATIONS

- Starter cord for any motor
- Flag Line
- Tree pruner Cord



Standard lengths for starter cord is 200ft, 250ft, 500ft or 1000ft packaged on our reels.
Please contact us for additional information or specifications.

SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/250'	WEIGHT/250'
40024	3/32	2.4			0.79 LBS	0.36 KG
40028	7/64	2.8			0.97 LBS	0.44 KG
40032	1/8	3.2	500 LBS	226 KG	1.15 LBS	0.52 KG
40036	9/64	3.6			1.48 LBS	0.67 KG
40040	5/32	4.0			1.72 LBS	0.78 KG
40044	11/64	4.4			2.0 LBS	0.95 KG
40048	3/16	4.8	915 LBS	415 KG	2.6 LBS	1.19 KG
40052	13/64	5.2			3.0 LBS	1.39 KG
40056	7/32	5.6			3.1 LBS	1.44 KG
40064	1/4	6.4	1475 LBS	669 KG	3.5 LBS	1.62 KG

ATLANTIC BRAIDS LTD.
100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA
TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192