



STATIC KERMANTLE

Manufactured on a 32 carrier Kermantle braider these industrial climbing and decent ropes are static. The static characteristic is achieved by manufacturing the core of the rope with twisted polyester strands.

FEATURES

- Low elongation
- UV resistant
- Durable
- Abrasion resistant
- Hydrophobic
- High Strength

APPLICATIONS

Climbing & Descent Line

twisted core



Standard lengths are 600ft and 1200ft.

Please contact us for additional information including alternative colours or specifications.

SPECIFICATIONS

PRODUCT NO	INCH	MM	AVG. TENSILE	AVG. TENSILE	WEIGHT/1000'	WEIGHT/1000'
61048	3/16	4.8	1200 LBS	540 KG		
61064	1/4	6.4	2400 LBS	1100 KG		
61079	5/16	7.9	3800 LBS	1700 KG		
61090	11/32	9.0	4200 LBS	1900 KG		
61095	3/8	9.5	5800 LBS	2600 KG		
61111	7/16	11.1	6800 LBS	3000 KG		
61127	1/2	12.7	8800 LBS	3990 KG		
61143	9/16	14.3	10200 LBS	4600 KG		
61159	5/8	15.9	12500 LBS	5600 KG		
61191	3/4	19.1	15000 LBS	6800 KG		
61222	7/8	22.2				
61254	1	25.4				

ATLANTIC BRAIDS LTD.

100 CONCESSION #1, CHUTE-À-BLONDEAU, ONT, K0B 1B0, CANADA

TEL/TÉLÉ:(613) 674-2728, FAX/TÉLÉCOPIEUR:(613) 674-3192

www.atlanticbraids.com